

Release date: 04 Jul 2025

smartGAS.

MADE IN GERMANY



BASIC^{EVO} PRO Broadband

Infrared gas Sensor
Broadband Freon(R134a) 2000(1000)ppm
smartGAS item number: B3-712205-108xx

Product features:

- Non Dispersive Infra-Red (NDIR)
- Dual beam / Reference channel
- Measure 20 gases with one sensor
- Internal calibration curve for each Freon
- Dual range 2000 ppm and 1000 ppm select-able
- Maximal flexibility in installation
- Easy target gas selection

The **BASIC^{EVO}** NDIR gas sensor is used for ambient air monitoring using dual wavelength technology. It is designed for leak detection in small concentration ranges (ppm range) for wall mount detectors and room air monitoring devices. **BASIC^{EVO}** diffusion sensors advantages are a long lifetime, low detection limits, very slight drift, a large temperature range, a fast response time and low maintenance costs. The **BASIC^{EVO}** series is therefore the optimal solution for all applications in which an ambient air sensor should be reliable and at the same time simple in its handling.

Options

- Modulbox
- Ready to use transmitter version
- Connect Interface
- Calibration software
- Data Logger software
- Calibration and test gases
- USB adapter

Support

- Design-In support
- Customization:
 - Software
 - Protocols
 - Measuring ranges
 - Background gas optimizing
 - Interfaces

smartGAS Mikrosensorik GmbH
Huenderstrasse 1, 74080 Heilbronn, Germany
T +49 (0) 7131 797553-0
sales@smartgas.eu www.smartgas.aeu

smartGAS Sensor Technology Co., Ltd
Building 16, No. 59 Jiangnan Rd. CEDZ Changshu, Jiangsu, China
T +86 (0) 512-83380880
info@smartgas-cn.com www.smartgas-cn.com

General features

Measurement principle:	Non Dispersive Infra-Red (NDIR), dual wavelength
Measurement range:	0 ... 2000 ppm (1000 ppm adjustable)
Gas supply:	by diffusion (atmospheric pressure) 62 mm x 37 mm x 30 mm (L x W x H)
Mounting dimensions:	Other Dimensions : see Technical Drawing
Warm-up time (start up time):	< 2 minutes
Warm-up time (fade in finished):	< 11 minutes
Warm-up time (full specification):	< 30 minutes

Measuring response*

Response time (t90)**:	< 30 s
Digital resolution:	1 ppm
Detection limit (3 σ):	$\leq 1\%$ [FS]
Repeatability:	$\leq \pm 2\%$ [FS]
Linearity error (straight line deviation):	$\leq \pm 2\%$ [FS] @R134a other see table on page 3
Long term stability (zero):	$\leq \pm 6\%$ [FS] over 12 month period
Long term stability (span):	$\leq \pm 5\%$ [FS] over 12 month period

Influence of T, P, flow rate, other*

Temp. dependence (zero):	$\leq \pm 0.3\%$ [FS] per °C
Temp. dependence (span):	$\leq \pm 0.6\%$ [FS] per °C
Pressure dependence:	+ 0.1 % [FS] of actual reading / hPa

Electrical parameters

Supply voltage:	3.3V .. 6.0V DC
Supply current (peak):	< 400mA @ 3.3V, < 240mA @ 5.0V
Inrush current:	< 600mA
Average power consumption:	< 800mW
Digital output signal:	Modbus ASCII / RTU via UART, autobaud, autoframe
Calibration:	zero and span by software

Climatic conditions

Operating temperature:	-20 .. + 40 °C
Storage temperature:	-20 .. + 60 °C
Air pressure:	800 .. 1150 hPa
Ambient humidity:	0 .. 95 % relative humidity (not condensing)

* Typical values related to 1013 hPa, Ta = 22 °C, flow = 0.7 l / min for dry (not condensing) and clean sample gas.
Stated values exclude calibration gas tolerance.

Broadband Freon Table : Article code B3-712205-10801

Freon type	Freon index:	Linearity error (3 σ) With R134a span calibration	Linearity error (3 σ) With target gas calibration
R22	0	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R23	1	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R32	2	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R123	3	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R125	4	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R404a	5	$\leq \pm 12\%$ [FS]	$\leq \pm 3\%$ [FS]
R407a	6	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R407c	7	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R407f	8	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R449a	9	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R410a	10	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R452a	11	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R454b	12	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R455a	13	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R507	14	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R513a	15	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R515b	16	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R1233zd	17	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R1234yf	18	$\leq \pm 15\%$ [FS]	$\leq \pm 3\%$ [FS]
R1234ze	19	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]

* gas tables vary

Broadband Freon Table : Article code B3-712205-10802

Freon type	Freon index:	Linearity error (3 σ) With R134a span calibration	Linearity error (3 σ) With target gas calibration
R22	0	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R11	1	$\leq \pm 30\%$ [FS]	$\leq \pm 7\%$ [FS]
R32	2	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R152a	3	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R218	3	$\leq \pm 20\%$ [FS]	$\leq \pm 4\%$ [FS]
R404a	5	$\leq \pm 12\%$ [FS]	$\leq \pm 3\%$ [FS]
R245fa	6	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R407c	7	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R422d	8	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R449a	9	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R410a	10	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R472a	11	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R472b	12	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R508b	13	$\leq \pm 15\%$ [FS]	$\leq \pm 3\%$ [FS]
R507	14	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R513a	15	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R512a	16	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R514a	17	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]
R1234yf	18	$\leq \pm 15\%$ [FS]	$\leq \pm 3\%$ [FS]
R1234ze	19	$\leq \pm 10\%$ [FS]	$\leq \pm 3\%$ [FS]

* gas tables vary

All rights reserved. Any logos and/or product names are trademarks of smartGAS. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of smartGAS is strictly prohibited. All specifications – technical included – are subject to change without notice. Depending on the application, the target gas and the measurement range the technical data may differ. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale.

For more information, please visit www.smartgas.eu or contact us at sales@smartgas.eu

Please consult smartGAS sales for parts specified with other temperature and measurement ranges. At first initiation and depending on application and ambient conditions recalibration is recommended. Recurring cycles of recalibration are recommended.