

MADE IN GERMANY



ANAREX (-DS) 2.0

Multigas Analyzer
#2-N21-N22 #2-ML50
CO2 10 Vol.% CO 1 Vol.% // O2 25 Vol.%

Product features:

- High stable measuring performance
- Easy operation via touch screen
- Simple sensor calibration
- Standard 19 inch 3HE rack
- Analog and digital output
- Low maintenance and high durability
- High selectivity and measuring accuracy
- Long-term stability and very low drift
- Low detection limit and T90 time



The **ANAREX** product family impresses with its stable high-precision measuring performance, intuitive operation and easy calibration. Designed as a 19-inch multi-gas analyzer, the **ANAREX** is available even with two gas streams as **ANAREX-DS** (double stream) as two in one solution. **ANAREX** gas analyzers are primarily based on the NDIR sensors of the **FLOW^{EVO}** and **SILAREX** series, however, they can be supplemented with several technologies like NDUV, TCD, TDLS, EC, PID, paramagnetic and photoacoustic as well as several other.

General features

Release date: 26. Aug 2024

Multi Gas Analyzer

Gas Streams:	1		
Gas supply:	Flow Mode 1/8" NPTF		
Mounting dimensions:	Standard 19" 3 U		
User Interface:	Touch panel, 5.6" TFT		
Gas Inlet Flow	0.5 .. 0.8 L/min (Flow fluctuations ≤0.02 L/min)		
Inlet Gas Temp.	5 .. 35 °C		
Inlet Gas Pressure	116 kPa (max)		
Moisture in Gas	inlet gas dew point: 5 °C ±0.1 °C		
Dust in gas flow	100 µg/m ³ , ≤ 1µm		
Warm-up time (full specification):	< 30 minutes		
Flow Meter	2		
Internal Gas Tubing	PU (certified)		
Zero Calibration Gas	Stream 1 : Nitrogen	Stream 2 : Nitrogen	
Span Calibration Gas Background	Stream 1 : Nitrogen	Stream 2 : Nitrogen	

Measuring*

Response time (t90) @ 0.7 l / min:	≤ 20 s					
Gas	Technology	Range	Linearity Error	Display	Compensated by	Stream
1 CO2	NDIR	0 .. 10 Vol.%	±1 %[FS]	XX.x		1
2 CO	NDIR	0 .. 1 Vol.%	±1 %[FS]	X.xx	1	1
3 O2	PM-LN (Low Noise)	0 .. 25 Vol.%	±0.5 %[FS]	XX.xx		2
4						
5						
O2 30 min drift:	< 0.01% (air)					

Electrical parameters

Supply voltage:	198~242V AC, 50/60 Hz
Power Connector	EN60320 C1
Case Protection Level	IP42 (EN60529)
Package Dimensions	577mm*512mm*255mm

Climatic conditions

Operating temperature:	5 °C .. 45 °C
Storage temperature:	-20 .. + 60 °C
Air pressure:	760 .. 1160 hPa
Ambient humidity:	0 .. 95 % relative humidity (not condensing)

Accessories to be ordered separately :

Power Cable:	Refer to the requirement of country
Gas Connections (one Set : Inlet/Outlet)	Stainless Steel: 1/8" 1/4" 10mm 6mm Rubber Tube: 6mm PTFE: 6mm

* Typical values related to 1013 hPa, Ta = 22 °C, flow = 0.7 l / min for dry (not condensing) and clean sample gas.
Stated values exclude calibration gas tolerance.

All rights reserved. Any logos and/or product names are trademarks of smartGAS. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of smartGAS is strictly prohibited. All specifications – technical included – are subject to change without notice. Depending on the application, the target gas and the measurement range the technical data may differ. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale.

For more information, please visit www.smartgas.eu or contact us at sales@smartgas.eu

Please consult smartGAS sales for parts specified with other temperature and measurement ranges. At first initiation and depending on application and ambient conditions recalibration is recommended. Recurring cycles of recalibration are recommended.