





MADE IN GERMANY



SILAREX

Low Range NDIR Gas Sensor for CO
CO 1000 ppm
smartGAS item number: SX-100006-00000

- Ready to use calibrated
- On board cross compensation
- On board pressure compensation
- Modbus ASCII/RTU, autobaud, autoframe
- Status indicated by LED



Application Examples

Emission monitoring CEMS
Biogas
Process measurement

Accessories

Insulation housing
Gas cooler
Particle filter
Gas pump
Mounting equipment

Available design in support

Mechanical Installation
Data communication
Gas pre-treatment

General features

Channel 1:

Measurement principle:	Non Dispersive Infra-Red (NDIR), dual wavelength	
Target gas:		CO
Measurement range:	0 ... Full Scale (FS)	FS = 1000 ppm
Gas supply:	by flow (nearly atmospheric pressure)	
Flow rate:	0.1 ... 1.0 l / min	
Mounting dimensions:	336 mm x 40 mm x 55 mm (L x W x H)	
Warm-up time:	< 2 minutes (start up time) < 30 minutes (full specification)	

Measuring response*

Response time (t ₉₀) @ 0.7 l / min:	< 4 s (fast), < 8 s (medium), < 60 s (slow)	
Digital resolution:		0.1 ppm
Detection limit (3 σ) max.:	in fast / medium / slow mode:	6 ppm / 4 ppm / 2 ppm
Repeatability:		≤ ± 6 ppm
Linearity error (straight line deviation):		≤ ± 10 ppm
Long term stability (zero):	after 1000 h operating time	≤ ± 10 ppm
Long term stability (span):	after 1000 h operating time	≤ ± 20 ppm

Influence of T, P, flow rate, other*

Temp. dependence (zero):	with thermal isolation, heater on	≤ ± 0.1 ppm per °C
Temp. dependence (span):	with thermal isolation, heater on	≤ ± 0.2 ppm per °C
Pressure dependence:	pressure compensated, residual error in % of actual reading / hPa	≤ ± 0.02
Flow rate dependence per 0.1 l / min:		≤ ± 2 ppm
Gas dew point requirement:	particle free and clean sample gas	< + 5°C dew point (stable)

Electrical inputs and outputs

Supply voltage:	24 V DC ± 10 %	
Average power consumption	< 6 W (while heater on) // < 1 W (at stabilized temperature)	
Inrush current:	< 400 mA	
Digital output signal	Modbus ASCII / RTU via RS485, autobaud, autoframe	
Calibration	Zero and Span via Modbus ASCII / RTU	

Climatic conditions

Sensor heating temperature	42 °C
Operating ambient temperature:	appr. + 10 ... + 40 °C (thermal isolation required)
Storage temperature:	-20 °C ... + 60 °C
Air pressure:	800 ... 1150 hPa
Ambient humidity:	0 ... 95 % rel. H. (not condensing)

* Typical values related to 1013 hPa, Ta = 22 °C, flow = 0.7 l / min for dry (not condensing) and clean sample gas. Stated values exclude calibration gas tolerance.

All rights reserved. Any logos and/or product names are trademarks of smartGAS. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of smartGAS is strictly prohibited. All specifications – technical included – are subject to change without notice. Depending on the application, the target gas and the measurement range the technical data may differ. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale.

For more information, please visit www.smartgas.eu or contact us at sales@smartgas.eu

Please consult smartGAS sales for parts specified with other temperature and measurement ranges. At first initiation and depending on application and ambient conditions recalibration is recommended. Recurring cycles of recalibration are recommended.