





MADE IN GERMANY



SILAREX

NDIR Multi-Gas Sensor for CEMS
 CO₂ 20 Vol.-% // CO 5 Vol.-%
 smartGAS item number: SX-200012-00000

- CEMS Dual Gas NDIR sensor
- 2 active measurement channels
- Ready to use calibrated
- On board cross compensation
- On board pressure compensation
- Modbus ASCII/RTU, autobaud, autoframe
- Status indicated by LED



Application Examples

Emission monitoring CEMS
 Biogas
 Process measurement

Available as

2-Channel
 3-Channel

Accessories

Insulation housing
 Gas cooler
 Particle filter
 Gas pump
 Mounting equipment

Available design in support

Mechanical Installation
 Data communication
 Gas pre-treatment

SILAREX | CO₂ // CO | SX-200012-00000

General features		Channel 1:	Channel 2:
Measurement principle:	Non Dispersive Infra-Red (NDIR), dual wavelength		
Target gas:		CO ₂	CO
Measurement range:	0 ... Full Scale (FS)	FS = 20 Vol.-%	FS = 5 Vol.-%
Gas supply:	by flow (nearly atmospheric pressure)		
Flow rate:	0.1 ... 1.0 l / min		
Mounting dimensions:	336 mm x 40 mm x 55 mm (L x W x H)		
Warm-up time:	< 2 minutes (start up time) < 30 minutes (full specification)		

Measuring response*

Response time (t ₉₀) @ 0.7 l / min:	< 4 s (fast), < 8 s (medium), < 60 s (slow)		
Digital resolution:		0.01 Vol.-%	1 ppm
Detection limit (3 σ) max.:	in fast / medium / slow mode:	0.04 Vol.-% / 0.02 Vol.-% / 0.01 Vol.-%	0.006 Vol.-% / 0.003 Vol.-% / 0.002 Vol.-%"
Repeatability:		≤ ± 0.07 Vol.-%	≤ ± 0.51 Vol.-%
Linearity error (straight line deviation):		≤ ± 0.2 Vol.-%	≤ ± 0.05 Vol.-%
Long term stability (zero):	after 1000 h operating time	≤ ± 0.05 Vol.-%	≤ ± 0.02 Vol.-%
Long term stability (span):	after 1000 h operating time	≤ ± 0.20 Vol.-%	≤ ± 0.10 Vol.-%

Influence of T, P, flow rate, other*

Temp. dependence (zero):	with thermal isolation, heater on	n.a.	n.a.
Temp. dependence (span):	with thermal isolation, heater on	n.a.	n.a.
Pressure dependence:	pressure compensated, residual error in % of actual reading / hPa	≤ ± 0.02	≤ ± 0.02
Flow rate dependence per 0.1 l / min:		≤ ± 0.02 Vol.-%	≤ ± 0.005 Vol.-%
Cross sensitivity (zero) other gases:	"@ 20 Vol.-% CO ₂ (compensated for 42 °C): @ 5 Vol.-% CO (compensated for 42 °C):"	"-" ≤ ± 0.2 Vol.-%"	"≤ ± 0.05 Vol.-%" "-"

Electrical inputs and outputs

Supply voltage:	24 V DC ± 10 %
Average power consumption	< 6 W (while heater on) // < 1 W (at stabilized temperature)
Inrush current:	< 400 mA
Digital output signal	Modbus ASCII / RTU via RS485, autobaud, autoframe
Calibration	Zero and Span via Modbus ASCII / RTU

Climatic conditions

Sensor heating temperature	42 °C
Operating ambient temperature:	appr. + 10 ... + 40 °C (thermal isolation required)
Storage temperature:	-20 °C ... + 60 °C
Air pressure:	800 ... 1150 hPa
Ambient humidity:	0 ... 95 % rel. H. (not condensing)

* Typical values related to 1013 hPa, Ta = 22 °C, flow = 0.7 l / min for dry (not condensing) and clean sample gas. Stated values exclude calibration gas tolerance.

All rights reserved. Any logos and/or product names are trademarks of smartGAS. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of smartGAS is strictly prohibited. All specifications – technical included – are subject to change without notice. Depending on the application, the target gas and the measurement range the technical data may differ. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein. The data is given for guidance only. It does not constitute a specification or an offer for sale.

For more information, please visit www.smartgas.eu or contact us at sales@smartgas.eu

Please consult smartGAS sales for parts specified with other temperature and measurement ranges. At first initiation and depending on application and ambient conditions recalibration is recommended. Recurring cycles of recalibration are recommended.